



R6805 STUD ADHESIVE

PRODUCT DESCRIPTION

R6805 is a water based synthetic adhesive used for bonding plasterboard to timber and metal studs for wall and ceiling linings. Its buttery consistency is designed for easy no-slump application, fast grab and maximum adhesive transfer. It is used in a wide range of climatic conditions.

The R6805 Stud Adhesive passes all requirements of the Australian Standard AS2753-1985.

SURFACE PREPARATION:

Studs should be dry and free of oil and as dust free as possible.

SPECIFICATION:

<i>Wet Colour</i>	<i>Blue as per colour standard</i>
<i>Appearance</i>	<i>Free from microbial soilage and major separation</i>
<i>Base</i>	<i>Synthetic Emulsion</i>
<i>Solids</i>	<i>72 - 75%</i>
<i>Viscosity Heliopath #F/5rpm/25°C</i>	<i>900,000 - 1,200,000 cps</i>
<i>pH</i>	<i>7.5 - 8.5</i>
<i>S.G.</i>	<i>1.35 - 1.45</i>
<i>Clean Up</i>	<i>Warm soapy water</i>
<i>Shelf Life</i>	<i>Up to 12 months in sealed containers at specified storage temperatures</i>

THIS PRODUCT IS LOW IN TOXICITY

APPLICATION

All surfaces to be bonded should be dry, free of dust, grease, oil or other foreign matter.

Plasterboard linings should be fixed within 30 minutes of application of adhesive.

R6805 Stud Adhesive must be used in conjunction with nails or screws. It does not constitute a fixing system on its own.

SAFETY DIRECTIONS

Storage

For optimum shelf life store in tightly closed, original containers out of direct sunlight between 15 and 25°C. Do not freeze.

Disposal

Please dispose of empty bottles containers and residue in accordance with your local waste management regulations.

First Aid

In use, please ensure that Occupational Health and Safety requirements are observed.

Eyes: Irrigate with water for 15 minutes and see a doctor.

Skin: Wash off with warm water and soap

If swallowed, give plenty of water. Do not induce vomiting. Seek medical attention.

Material Safety Data Sheet available upon request

Issued: April 2007

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia
P.O. Box 147, Kilsyth, Victoria 3137 Australia
Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009
E-mail: info@rlapolymers.com.au

 A British Vita Group Company



67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand
Telephone: (9) 268 0301
Facsimile: (9) 268 0305