



Fine Patch 35

Levelling Powders

35



Roberts Fine Patch 35 is a fast drying cementitious underlayment designed for smoothing ridges, patching cracks or holes and featheredge transitions.

Advantages

- Easy to use - just add water
- Primerless
- Does not require the addition of latex
- High adhesion
- Fast Setting

Sub Floor Preparation

Sub floor must be free of oil, grease, wax, curing compounds, dust, old adhesive and any other contaminations, which may inhibit bond.

Note:

Concrete floors must be dry in accordance with A.S. 1884 - 1985 Appendix A 70% Relative humidity maximum.

Mixing

Place a small amount of clean water in to a clean pail, then add small amount of powder while mixing to achieve the desired consistency.

Application

Apply the mixed compound to the substrate using a trowel. Can be applied from featheredge to 3mm thickness.

Imperfections or minor trowel ridges can be removed after 1 hour by gentle sanding. Allow to dry before installing floor coverings - wipe any sanded areas with a damp cloth to remove dust prior to installing floor coverings.

Clean Up

Clean all equipment with water immediately after use.

Packaging

5 Kg pails.

Storage

Fine Patch 35 is a cement-based product, which must be stored in a dry area off the ground and out of direct sun light.

Coverage

Approximately 4 sq.m@ 1mm thickness per 5 Kg pail. Applied as a feather edge, expect to gain anything up to 30 sq.m depending on texture of substrate.

Shelf Life

6 months in dry condition

Safety & Handling

Material Safety Data Sheet available upon request.